



VA950 - SUPRA FLAT WHITE/ PASTEL



Date of compilation: 8/9/2021

Version: 1

SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** VA950 - SUPRA FLAT WHITE/ PASTEL
Other means of identification:
Non-applicable
- 1.2 Recommended use of the chemical and restrictions on use:**
Relevant uses: Acrylic paint
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**
Lanco & Harris Corp.
600 Mid Florida Drive Airport Industrial Park
32824 Orlando - Florida - United States
Phone.: 407-240-4000 - Fax: 407-240-4000
info@lancopaints.com
http://www.lancopaints.com
- 1.4 Emergency phone number:** CHEMTREC (US Transportation) +1-800-262-8200| CHEMTREC (International Transportation) +1-703-741-5500

SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
NFPA:
Health Hazards: 0
Flammability Hazards: 0
Instability Hazards: 0
Special Hazards: Non-applicable
29 CFR 1910.1200:
Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.
Carc. 1B: Carcinogenicity, Category 1B, H350
- 2.2 Label elements:**
NFPA:

29 CFR 1910.1200:
Danger

Hazard statements:
Carc. 1B: H350 - May cause cancer.
Precautionary statements:
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P308+P313: IF exposed or concerned: Get medical advice/attention.
P405: Store locked up.
P501: Dispose of the contents/containers according to the local, state and federal regulations.
Substances that contribute to the classification
Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$); Quartz (1 % < RCS < 10%)
- 2.3 Hazards not otherwise classified (HNOC):**
Non-applicable

- CONTINUED ON NEXT PAGE -



VA950 - SUPRA FLAT WHITE/ PASTEL

Date of compilation: 8/9/2021

Version: 1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:





Non-applicable

3.2 Mixtures:

Chemical description: Aqueous mixture composed of chemical products for cleaning products

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 7732-18-5	Water	25 - <50 %
CAS: 1317-65-3	Limestone	10 - <25 %
CAS: 92704-41-1	Kaolin, calcined	10 - <25 %
CAS: 13463-67-7	Titanium dioxide (aerodynamic diameter ≤ 10 µm) Carc. 2: H351 - Warning	 2.5 - <10 %
CAS: Non-applicable	Vinyl acrylic copolymer	2.5 - <10 %
CAS: 57-55-6	Propane-1,2-diol	<1 %
CAS: 14808-60-7	Quartz (1 % < RCS < 10%) Carc. 1B: H350; STOT RE 2: H373 - Danger	 <1 %
CAS: 51200-87-4	4,4-dimethyloxazolidine Acute Tox. 4: H302+H312+H332; Eye Irrit. 2A: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	  <1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or shower the person affected if necessary thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

- CONTINUED ON NEXT PAGE -



VA950 - SUPRA FLAT WHITE/ PASTEL

Date of compilation: 8/9/2021

Version: 1

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

- CONTINUED ON NEXT PAGE -

VA950 - SUPRA FLAT WHITE/ PASTEL

Date of compilation: 8/9/2021

Version: 1

SECTION 7: HANDLING AND STORAGE (continued)

A.- Technical measures for storage

Minimum Temp.:	35.01 °F
Maximum Temp.:	100 °F
Maximum time:	24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) CAS: 13463-67-7	8-hour TWA PEL		15 mg/m ³
	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values:

Identification	Occupational exposure limits		
Limestone CAS: 1317-65-3	TLV-TWA		10 mg/m ³
	TLV-STEL		20 mg/m ³
Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) CAS: 13463-67-7	TLV-TWA		10 mg/m ³
	TLV-STEL		
Quartz (1 % < RCS < 10%) CAS: 14808-60-7	TLV-TWA		0.025 mg/m ³
	TLV-STEL		

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:


Identification	Occupational exposure limits		
Quartz (1 % < RCS < 10%) CAS: 14808-60-7	PEL		0.05 mg/m ³
	STEL		

8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

C.- Specific protection for the hands


- CONTINUED ON NEXT PAGE -

VA950 - SUPRA FLAT WHITE/ PASTEL

Date of compilation: 8/9/2021


Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Pictogram	PPE	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Ocular and facial protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

National volatile organic compound emission standards (40 CFR Part 59):

V.O.C. (Subpart C - Consumer):	1.04 % weight
V.O.C. (Coatings) at 68 °F:	44 kg/m ³ (44 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F:	Liquid
Appearance:	Viscous
Color:	According to the markings on the package
Odor:	Mild
Odour threshold:	Non-applicable *

Volatility:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



VA950 - SUPRA FLAT WHITE/ PASTEL

Date of compilation: 8/9/2021

Version: 1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Boiling point at atmospheric pressure:	214 °F
Vapour pressure at 68 °F:	Non-applicable *
Vapour pressure at 122 °F:	12321.07 Pa (12.32 kPa)
Evaporation rate at 68 °F:	Non-applicable *

Product description:

Density at 68 °F:	Non-applicable *
Relative density at 68 °F:	Non-applicable *
Dynamic viscosity at 68 °F:	Non-applicable *
Kinematic viscosity at 68 °F:	Non-applicable *
Kinematic viscosity at 104 °F:	>20.5 cSt
Concentration:	Non-applicable *
pH:	8.5 - 9.5
Vapour density at 68 °F:	Non-applicable *
Partition coefficient n-octanol/water 68 °F:	Non-applicable *

Solubility in water at 68 °F:	
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

Flammability:

Flash Point:	Non Flammable (>199.4 °F)
Heat of combustion:	Non-applicable *
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	790 °F
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Explosive:

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

9.2 Other information:

Surface tension at 68 °F:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction

Contact with air

Increase in temperature

Sunlight

Humidity

- CONTINUED ON NEXT PAGE -



VA950 - SUPRA FLAT WHITE/ PASTEL

Date of compilation: 8/9/2021

Version: 1

SECTION 10: STABILITY AND REACTIVITY (continued)

Not applicable	Not applicable	Precaution	Precaution	Not applicable
----------------	----------------	------------	------------	----------------

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
IARC: Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) (2B); Quartz (1 % < RCS < 10%) (1)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -



VA950 - SUPRA FLAT WHITE/ PASTEL

Date of compilation: 8/9/2021

Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) CAS: 13463-67-7	LD50 oral	10000 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Limestone CAS: 1317-65-3	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
4,4-dimethyloxazolidine CAS: 51200-87-4	LD50 oral	950 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	Non-applicable	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Identification	Acute toxicity		Species	Genus
Propane-1,2-diol CAS: 57-55-6	LC50	51400 mg/L (96 h)	Pimephales promelas	Fish
	EC50	10000 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	19100 mg/L (336 h)	Selenastrum capricornutum	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Propane-1,2-diol CAS: 57-55-6	BOD5	1.08 g O ₂ /g	Concentration	100 mg/L
	COD	1.63 g O ₂ /g	Period	28 days
	BOD5/COD	0.66	% Biodegradable	90 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Propane-1,2-diol CAS: 57-55-6	BCF	1
	Pow Log	-0.92
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Propane-1,2-diol CAS: 57-55-6	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3.547E-2 N/m (77 °F)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

- CONTINUED ON NEXT PAGE -



VA950 - SUPRA FLAT WHITE/ PASTEL

Date of compilation: 8/9/2021

Version: 1

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See epigraph 6.2.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Part 261- IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

SARA Title III - Toxic Chemical Release Inventory Reporting (Section 313): Non-applicable

California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986): Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) ; Quartz (1 % < RCS < 10%)

The Toxic Substances Control Act (TSCA) : Water ; Limestone ; Kaolin, calcined ; Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) ; Propane-1,2-diol ; Quartz (1 % < RCS < 10%) ; 4,4-dimethyloxazolidine

Massachusetts RTK - Substance List: Limestone ; Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) ; Quartz (1 % < RCS < 10%)

New Jersey Worker and Community Right-to-Know Act: Limestone ; Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) ; Propane-1,2-diol ; Quartz (1 % < RCS < 10%)

New York RTK - Substance list: Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$)

Pennsylvania Worker and Community Right-to-Know Law: Limestone ; Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) ;

Propane-1,2-diol ; Quartz (1 % < RCS < 10%)

CANADA-Domestic Substances List (DSL): Water ; Kaolin, calcined ; Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) ; Propane-1,2-diol ; Quartz (1 % < RCS < 10%) ; 4,4-dimethyloxazolidine

CANADA-Non-Domestic Substances List (NDSL): Limestone

NTP (National Toxicology Program): Quartz (1 % < RCS < 10%)

Minnesota - Hazardous substances ERTK: Limestone ; Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) ; Quartz (1 % < RCS < 10%)

Rhode Island - Hazardous substances RTK: Limestone ; Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) ; Propane-1,2-diol ; Quartz (1 % < RCS < 10%)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Quartz (1 % < RCS < 10%)

Hazardous Air Pollutants (Clean Air Act): Non-applicable

Hazardous substances release notification under CERCLA sections 102-103 (40 CFR Part 302): Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

H350: May cause cancer.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

29 CFR 1910.1200:

- CONTINUED ON NEXT PAGE -



VA950 - SUPRA FLAT WHITE/ PASTEL

Date of compilation: 8/9/2021

Version: 1

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.

Carc. 1B: H350 - May cause cancer.

Carc. 2: H351 - Suspected of causing cancer (Inhalation).

Eye Irrit. 2A: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

STOT SE 3: H335 - May cause respiratory irritation.

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET